Form Approved REPORT DOCUMENTATION PAGE OMB No. 0704-0188 Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. 1. REPORT DATE (DD-MM-YYYY) 2. REPORT TYPE 3. DATES COVERED (From - To) 16 May 2003 Technical Abstract 4. TITLE AND SUBTITLE 5a. CONTRACT NUMBER Graphical User Interface for Controlling the Execution of ROCETS Liquid Rocket 5b. GRANT NUMBER **Engine Simulations** 5c. PROGRAM ELEMENT NUMBER 6. AUTHOR(S) 5d. PROJECT NUMBER 4847 Wendel M. Burkhardt, Robert LeMoyne, Jonathon Ulmer 5e. TASK NUMBER 02ET 5f. WORK UNIT NUMBER 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) 8. PERFORMING ORGANIZATION REPORT NUMBER Advatech Pactific, Inc. Technology Development & Support AFRL-PR-ED-AB-2003-134 205 Park Ave., Suite 8 Redlands, CA 92373 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) 10. SPONSOR/MONITOR'S ACRONYM(S) Air Force Research Laboratory (AFMC) AFRL/PRS 11. SPONSOR/MONITOR'S 5 Pollux Drive NUMBER(S) Edwards AFB CA 93524-7048 AFRL-PR-ED-AB-2003-134 12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited. 13. SUPPLEMENTARY NOTES 14. ABSTRACT

20030617 141

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Sheila Benner
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code)
Unclassified	Unclassified	Unclassified	A		(661) 275-5693

15. SUBJECT TERMS



MEMORANDUM FOR PRS (Contractor Publication)

FROM: PROI (STINFO)

20 May 2003

(Statement A)

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-AB-2003-134

Wendel M. Burkhardt; Robert LeMoyne; Jonathon Ulmer (Advatech Pacific, Inc.), "Graphical User Interface for Controlling the Execution of ROCETS Liquid Rocket Engine Simulations" (abstract only)

JANNAF December 2003 CS/APS/PSHS/MSS Conference (no location provided, December 2003) (Deadline = 10 March 2003 = Past Due)

December 2003 CS / APS / PSHS / MSS ABSTRACT SUBMITTAL FORM

Unclassified Abstract

(250-300 words; do not include figures or tables)

The ROCETS (ROCket Engine Transient Simulation) computer program is a very powerful tool for state-of-the-art modeling and simulation of liquid rocket engines. The versatility and adaptability of this tool makes it ideal for the analysis of any type of liquid rocket engine cycle at any level of modeling detail desired by the user. While these features make ROCETS a very powerful tool, they also make it a very difficult tool for casual users to apply to problems effectively. This problem exists both for the actual development of the computer model as well as the operation of a working model.

This paper describes a novel Graphical User Interface (GUI) developed specifically to address the problem of simplifying the use of working ROCETS models. The GUIs described provide an interface to two specific ROCETS liquid engine models, both using variations of an oxidizer rich staged combustion cycle. The GUIs translate inputs familiar to rocket engineers into inputs suitable for the ROCETS models, freeing the user from performing the numerous tedious calculations required to obtain the hundreds of input parameters needed. The GUI permits users to input top-level parameters such as thrust, chamber pressure, nozzle expansion ratio, inlet pressures, etc. These inputs are then used to resize all of the engine components. In this way, the user is able to resize the engine being considered over a thrust range of 10 Klbf to 2Mlbf. The GUI permits the user to perform trade studies rapidly and assess feasibility of specific design parameters and operating conditions. The interface also has the capability to vary input parameters automatically over a selected range and output the results graphically.

Approved for public release; distribution unlimited.